

Data Sheet

K Series
421.D.101.02

Switchable Analog Meters with Moving-Iron Movement

EQ 72 SWT
EQ 96 SWT

with Slide-In-Dial



WEIGEL

Application

The moving-iron panel meters **EQ 72/96 SWT** (K series) housed in moulded thermoplastic cases are used for the measurement of AC voltages in the usual 3-phase system.

Moving-iron meters indicate rms-values practically independent of wave form even of high harmonics. Error of indication may occur for extreme wave forms (e.g. phase gating controls) and / or frequencies above 100 Hz.

With the built-in 6 position switch, all voltages in a 4-wire 3-phase system can be measured.

Movements

Moving-iron movement with pivot suspension, spring loaded shock absorbing jewel bearings and silicon oil damping.

Mechanical Data

case details	moulded square case suitable to be mounted in control / switchgear panels, machine tool consoles or mosaic panels, stackable	
material of case	polycarbonate thermoplastics, flame retardant with UL rating of 94 V – 0	
material of window	glass ▶	
colour of bezel	black (similar to RAL 9005) ▶	
position of use	vertical $\pm 5^\circ$ ▶	
panel fixing	screw clamps or spring clamps	
mounting	stackable next to each other	
panel thickness	≤ 40 mm	
terminals	hexagon studs, M4 screws and wire clamps E3	
dimensions (in mm)	EQ 72 SWT	EQ 96 SWT
bezel	□ 72	□ 96
case	□ 66	□ 90
depth	53	53
panel cutout	□ 68 ^{+0.7}	□ 92 ^{+0.8}
weight approx.	0.19 kg	0.23 kg

Electrical Data

measuring unit	AC voltage / current
frequency range	16 ² / ₃ ... 100 Hz
power consumption	<4.5 VA
overload capacity (acc. to DIN EN 60 051 - 1)	
continuously	1.2 times rated voltage
5 s max.	2 times rated voltage, 1000 V max.
measurement category	CAT III
operating voltage	refer to Measuring Ranges
pollution level	2
enclosure code	IP 52 case front side IP 00 for terminals without protection against accidental contact IP 20 for terminals protected against accidental contact ▶

▶ also refer to "Options"

Measuring Ranges

AC voltage	500 V
operating voltage	600 V
for use on VT	N/100 V¹⁾
operating voltage	150 V

Please state transformer ratio when ordering.

¹⁾ full scale value = 1.2 times rated value (overload scaling)

switch positions in a 4-wire 3-phase system

6 switch positions	L1L3; L2L3; L1L2; L1N; L2N; L3N
--------------------	---------------------------------

Scaling

pointer	bar / knife-edge pointer	
pointer deflection	0 ... 90°	
scale characteristics	practically linear above 10% of rated full-scale value	
scale division	coarse-fine	
scale length	EQ 72 SWT 61 mm	EQ 96 SWT 97 mm
overload scaling (voltmeters for use on voltage transformers)	1.2 times rated voltage	

Accuracy at Reference Conditions


accuracy class	1.5 according to DIN EN 60 051 - 1
reference conditions	
ambient temperature	23°C
position of use	nominal position $\pm 1^\circ$ ▶
input	rated measuring value
wave form	sinusoidal, distortion factor ≤ 5%
frequency	45 ... 65 Hz
others	DIN EN 60 051 - 1

influences

ambient temperature	23°C ± 2K
position of use	nominal position $\pm 5^\circ$
frequency	15 ... 100 Hz
stray magnetic field	0.5 mT

Environmental

climatic suitability	climatic class 3 acc. to VDE/VDI 3540 sheet 2
operating temperature range	-10 ... +55°C
storage temperature range	-25 ... +65°C
relative humidity	≤ 75% annual average, non-condensing
shock resistance	15 g, 11 ms
vibration resistance	2.5 g, 5 ... 55 Hz



Switchable Analog Meters with Moving-Iron Movement

Rules and Standards

DIN 43 718	Measurement and control; front-frames and frontpanels of measurement and control equipment; principal dimensions
DIN 43 802	Line scales and pointers for indicating electrical measuring instruments; general requirements
DIN 16 257	Nominal positions and position symbols used for measuring instruments
DIN EN 60 051	Direct acting indicating analogue electrical measuring instruments and their accessories
-1	Part 1: Definitions and general requirements common to all parts
-2	Part 2: Special requirements for ammeters and voltmeters
-9	Part 9: Recommended test methods
DIN EN 60 529	Enclosure codes by housings (IP -code)
DIN EN 61 010 - 1	Safety requirements for electrical measuring, control and laboratory equipment Part 1: General requirements
DIN EN 61 326 - 1	Electrical equipment for measurement, control and laboratory use – EMC requirements Part 1: General requirements
DIN IEC 61 554	Panel mounted equipment – Electrical measuring instruments – Dimensions for panel mounting
VDE/VDI 3540 sheet 2	reliability of measuring and control equipment (classification of climates)

Options

case

window	non-glaring glass
colour of bezel	gray (similar to RAL 7037)
position of use	on request 15...165°

terminal safety protection

full - sized rear cover or protective sleeves to go on hexagon studs and M4 screws with wire clamps E3





dial

non-calibrated	with dial symbols
blank dial	pencil-marked on initial and end values
scale division and figuring	0 ... 100%
linear scale division	non-standard captions on request
additional lettering	on request e.g. "generator"
additional figuring	on request
coloured marks	red, green or blue for important scale values
coloured sector	red, green or blue within scale division
logo on the dial	none or on request



Connections

EQ 72 SWT

EQ 96 SWT



Dimensions



dimensions (in mm)	EQ 72 SWT	EQ 96 SWT
a	72	96
b	66	90
c	53	53
d	13	13

Ordering Information

type EQ	moving-iron panel meter, switchable
front dimensions 72 SWT 96 SWT	72 mm x 72 mm 96 mm x 96 mm
measuring ranges	refer to preceding table
window	glass ¹⁾ non-glaring glass
colour of bezel	black (similar to RAL 9005) ¹⁾ gray (similar to RAL 7037)
position of use	vertical ¹⁾ on request 15 ... 165° ²⁾
panel fixing	screw clamps ¹⁾ spring clamps
terminal safety protection	none ¹⁾ full-sized rear cover protective sleeves
dial	according to measuring range resp. standard series for use on transformers ¹⁾ non-calibrated, with dial symbols blank dial scale division and figuring 0 ... 100% according to standard series additional lettering on request ²⁾ additional figuring on request ²⁾ coloured marks red, green or blue ²⁾ coloured sector red, green or blue ²⁾
logo	WEIGEL ¹⁾ none OEM logo ²⁾

¹⁾ Standard

²⁾ Please clearly add the desired specifications.

ordering example

EQ 72 SWT, measuring range 0 ... 500 V, window non-glaring glass, WEIGEL logo

Weigel Meßgeräte GmbH

Postfach 720 154 • 90241 Nürnberg • Phone: 0911/42347-0
Erlenstraße 14 • 90441 Nürnberg • Fax: 0911/42347-39
Sales: Phone: 0911/42347-94
Internet: <http://www.weigel-messgeraete.de>
e-mail: vertrieb@weigel-messgeraete.de

– specifications subject to change without notice; date of issue 02/11 –

